



RoboMIG TBi RM 90W



Robot welding torch TBi RM 90W

Rating at 100% duty cycle (10 min. cycle)	
- Mixed gas:	19.0 kW (approx. 500 - 550 A)
Cooling method	2-circuit water cooling
Wire diameter	0.8 - 1.6 mm
Gas consumption	from 8 l/min
Gas flow	1 channel for protective and blow-out gas
Weight	approx. 0.70 kg
Technical specification	according to IEC 60974-7
Connection	TBi WH flange compatible to our WH cable assemblies, PowerPull wire feeders and quick-change

Torch rating will be reduced when using pulse-arc power sources.


adaptor.


Optimised protection by nozzle insulator and gas diffusor


Ordering information						
TBi RM 90W, Torch neck without consumables	universal 0°	for direct clampi 22°	ng 45°	for quick-change 22°	adaptor 45°	
Please order consumables sepa- rately as needed.	671P101231	671P101234	671P101235	671P101232	671P101233	












The TBi RoboMIG welding torch RM 90W has a very rugged design with a stainless steel outer tube. Therefore, the factory set TCP will neither be changed by thermal stresses during welding nor collisions. This fact greatly simplifies maintenance of the welding cell.

Due to large cross sections, this torch features specially good cooling properties.

When ordering, please make sure to choose the correct type for either direct clamping or for the chick-change adaptor. The torches are adjusted differently and must be used only for the corresponding mounting option.

Spare parts and consumables



Gas diffusor / nozzle insulator					
	30	Gas diffusor ceramic	671P102038		
	31	Nozzle insulator	346P019671		

JI O-IIIY 7.0XI.JIIIII		303F130070		
Accessories				
60	Open end wrench, size 13 mm	391P102026		

Standard equipment

* At the blank, please insert suitable information for wire diameter, e.g. 08 for 0.8 mm.

© 2008 TBi Industries GmbH. All rights reserved. Subject to change without notice. Warranty only when using original TBi consumables and spare parts. Excerpts and reprints not permitted. Nr. DOKP141072, 09/2008.

661P102014

TBi Industries GmbH Ruhberg 14 D-35463 Fernwald-Steinbach P.O. Box 67 D-35461 Fernwald-Steinbach

20 Tip holder M8, forced contact

Tel. + 49 6404 9171-0 Fax. + 49 6404 9171-40 Internet: www.tbi-industries.com E-mail: info@tbi-industries.com